

# SUNDRAY Virtual Wireless Access Controllers

## Product Overview

The SUNDRAY virtual wireless controllers are the devices which are independently researched and developed by SUNDRAY TECHNOLOGIES and has excellent performance, and integrates wireless controller, user authentication, marketing and promoting advertisement, consumer big data analysis, internet access management, flow control, firewall and internet management. etc. The Gigabit wireless controllers can manage all SUNDRAY AP, and have the following functions such as the seamless L2/L3 roaming, intelligent RF adjustment, diversified authentication methods, marketing advertisement push, elaborate management for user access behavior, flexible QoS control, optimization of the wireless protocol and the wired and wireless integration.

The wireless controllers support the local forwarding, and can be installed in any L2 or L3 network structure, which can reduce the complexity of the wireless configuration. SUNDRAY virtual wireless controllers create a safer/faster wireless network which supports the marketing advertisement push function.

Coordinated with the SUNDRAY wireless AP, it is positioned as the middle-sized WLAN access service, such as: The high speed WIFI is applied into the enterprises, chain supermarket, school, hotel, hospital, government, bank and scenic spot, etc.

## Product Features

### The unprecedented wireless access experience

#### ➤ L2/L3 seamless roaming

SUNDRAY virtual wireless controllers support the centralized forwarding and the local forwarding, and can be installed in any L2 and L3 network structure, and cross three layers; the configuration step is simplified. When the wireless user is roaming, the invariable IP address and the authentication state are ensured so as to provide the entire network seamless roaming within three layers.

#### ➤ Intelligent RF, comprehensively reduces the wireless interference.

The working channel and output power of the wireless access point are automatically adjusted; the real-time detection is performed on the surroundings to fully reduce the wireless interference, and improve the entire service quality of the wireless network.

#### ➤ Terminal dragging prevention and terminal's fair access

Terminal dragging prevention adopts the time fairness algorithm so that terminals with different rate occupy the same wireless channel time, which effectively solves the problems that the delay, suspended internet access and the low performance of the entire network.

#### ➤ Load balancing

Under the high-density users circumstance, the bandwidth usage ratio can be improved through the intelligent load balance based on the number of users, flow and frequency band so as to ensure the user to have an excellent experience of the network usage. Based on the load balance of the frequency band, the terminal

supporting the 2.4G/5G has the priority to access frequency band with 5GHZ.

## User Authentication

### ➤ Intelligent terminal identification

Intelligent terminal identification supports the mainstream operating system, such as ios, Andriod and windows, and pushing the WEB authentication page to terminals with most suitable-size screen after self adaptation, and avoiding multiple drags and adjusts the screen operation, which provides the user more intelligent using experience.

### ➤ Multiple flexible and safe authentication methods

The following authentication methods such as 802.1x, Portal, CA certificate, short message, we-chat, QR code audit, temporary visitor mode and the PSK are supported.

One-key configured instrument is independently researched and developed, which greatly simplifies the configuration step, and easily realizes the 802.1x authentication.

The value-added marketing function can be realized by collecting the relevant information about user through the short message and we-chat authentication without the cloud platform; compared with the cloud platform, the user data is safer.

### ➤ The authentication server is embedded inside, which easily realize the WEB authentication.

The Portal server is embedded inside the wireless controller, and can store 65,000 user account to great extent. The WEB authentication can be realized without the extra Portal server and Radius server, which easily realize the local authentication of the wireless user. The network configuration is simplified to reduce the cost for the network construction.

### ➤ Illegal AP countermeasure, and anti-phishing prevention

Illegal AP detection and elimination, eliminating phishing WIFI, carry-on WIFI and personal hotspot. By performing the real-time RF scan and detection on some characteristics (e.g., the MAC address of the specific SSID and AP, or the wireless signal transmitted by the AP managed by the wireless controller), the detected illegal access point is blocked so as to protect the confidential information about the user account and password.

## Marketing Advertisement Push

### ➤ Precision marketing of the user behavior

Based on the user behavior, the marketing push can match with the key words searched by the user in Google and Yahoo search engine collection, Amazon, Ebay and Jingdong to push the specific advertisement, and supports the web page floating window, we-chat and short message.

For example: When user uses the Safari to search “iPhone 6” in Google in the process of shopping, a Banner floating advertisement of the cell phone store from this mall will appear at the bottom of the web page.

### ➤ Advertisement pushing before and after authentication

Before the WEB authentication (including several authentication methods such as Portal, we-chat, short message and QR code), up to five full-screen advertisement illustration is played; the countdown method is supported;

after being forced to watch the advertisement display with a certain time, the user is allowed to access to internet;

Customers can set LOGO, background color, page word and disclaimer in WEB authentication page , and supports the switch between Chinese and English;

According to different SSID, access position, terminal type and time period, the authentication page can push different page content and set up different URL pages entered into after successful authentication.

#### ➤ **Flexible marketing advertisement push (on-line time, terminal appearance and initial access)**

The marketing push system is integrated inside the wireless controller, which supports the we-chat, short message and web page to perform the marketing push on the user. The information about the user is collected to realize actively advertisement push by the initial access, position alteration, on-line time, timing, terminal appearance and off-line; free advertisement marketing is realized by using WLAN, which is accurate, effective and truly realizes the O2O value-added marketing.

### **Consumer big data analysis**

#### ➤ **Consumer flow analysis**

The consumer flow analysis system is integrated inside the wireless controller, the separated region analyzes the number of the users, the accessing users, the new registered users who often enters into or firstly enters into or non-firstly enters into the shop in every day/the last 30 days/self-defined time period, and the average staying time, the distribution condition of the staying time and the entire consumer rate of returning back to the shop, from which the operator can directly know the condition of the consumer, and which provides the objective data evidence for the decision maker.

#### ➤ **Hot-spot map, people flow density**

The building structure map is uploaded to display the real deployment position of each AP in the form of diagram; the on-line condition of AP can be checked; the user list and real-time flow can be accessed; IT department knows the operation state of wireless network in each region so as to easily perform the operation. And can visually present the number of people of every corner with wireless coverage in a period of time by means of thermodynamic diagram and analyze the popular areas and lonely area.

### **Internet Access management**

#### ➤ **Flow control and improve the value of bandwidth**

Support virtual bandwidth channel and dynamic flow control, can allot different flow based on factors such as, user and time, flexibly allocate bandwidth resources, and maximize the value of bandwidth.

### **Wired and wireless integration**

#### ➤ **Wired and wireless integration**

Wired and wireless integration, support access authentication, access control, flow management, etc. for wired users; the one-stop service greatly reduces the cost of network construction.

#### ➤ **The exclusive AP Wired and wireless integration**

The controller supports the unified management of the AP wired port, can provide unified management of

accessed wired and wireless users, and maintain consistency with wireless side in access authentication, access control, flow management.

➤ **WEB unified and centralized management**

It realizes management and monitor of the whole network without deployment of desktop network management software. It provides friendly Web management interface and centralized control of all AP. There is no configuration at AP terminal. The AC sends configuration to all AP for unified updating of firmware. It can make AP grouping management in accordance with the area and location, support to check the AP work status, the number of access, flow velocity and so on, and realize unified and centralized configuration management and network operations for all the AP. And have the functions of managing access status, access management, online user state, equipment utilization, roaming record, , etc.

## Technical specifications

### Software specifications

Software specifications		
Item	Support features	NAC-100I
Basic performances	The default management AP number	2
	Maximum number of management AP (Bridge mode)	256
	License step size	1
	The maximum number of online concurrent users	5000
	Built-in local certification account number	65000
	VLAN quantity	4094
	ESSID quantity	32
Wireless foundation	802.11 protocol stack	Support 802.11a/b/g/n/ac
	Virtual AP	Supported
	Chinese SSID	Supported
	Hidden SSID	Supported
	Code deployment of various countries	Supported
	Isolation of wireless user	A second segregation and isolation function based on SSID
	On line detection	AP and online detection function of user
	Forced disconnection of wireless user	Supported
	No flow automatic aging of user	Supported
	802.11 ac 80 MHZ information channel binding	Supported
	20 MHZ / 40 MHZ automatic switching of 40 MHZ model	Supported
Data forward	Local forward	Supported
Roaming	the second and third layer of roaming within the same AC under different AP.	Supported
	the second and third layer of roaming between different AC under different AP.	Supported
Access authentication	Authentication type	Support WPA-PSK, WPA2-PSK, and WPA-PSK/WPA2-PSK mixed encryption, open + web authentication, WPA-PSK/WPA2-PSK+web authentication, WPA (enterprise), WPA2 (enterprise), WPA/WPA2 (enterprise)
	802.1 x authentication	Support 802.1 x one-key automatic configuration deployment and support 802.1 x non-awareness certification, which only needs to download one-key automatic configuration tool when accessing for the first time, to quickly complete the wireless network configuration, greatly reducing the network deployment work.
	Portal authentication	Support intelligent identification terminal type, provide matching page with suitable size for different terminals, support custom page logo, display information, etc., and support setting verification, certification interval and time threshold for off-line re-connection and re-certification.
	QR code audit certification	Once visitor terminal is accessed to the wireless network, the terminal will automatically pop up QR code page, and the reviewer scans the QR code of visitor terminal by mobile phone to surf the Internet. And record the visitor user by the reviewer+ note + visitor terminal MAC three dimension, which can be traced and guarantee the network security.

	WeChat certification	After accessing wi-fi, the user can scan the QR code of shopping mall or corporate public ID to log in. The one-key log in function can complete deployment without any code development. In addition, We Chat certification supports clicking on text messages Internet link, clicking on the menu bar to view ads online, and We Chat aouth authorized log in.
	Text message certification	Support certification effective permanently. That is, it needs certification by text message for the first access, and the subsequent access needs no certification. This saves cost of text message and improves the user's online experience.
	Temporary visitor authentication	It is internally installed with a temporary user information management system, by which a temporary user can log in during the effective period; It is internally installed with secondary authority system for temporary account management, which can only be used for creation and management of temporary account; Support to print QR code of temporary visitors, and temporary visitors can scan QR code to get to the Internet; Support grouping of temporary visitors;
	Free user authentication	Support to only show portal pages, just click the log in button to get to the Internet with no need to input ID and password and without certification;
	CA certificate authentication	It is internally installed with CA certificate issuing center, can realize safe authentication certificate with no need to set up certificate server (at the same time support external certificate server for import certification)
	Local account authentication	Support 802.1 x, Portal authentication
	The external authentication database	Support related external RADIUS, LDAP, Active Directory, achieve authentication of 802.1 x, Portal, etc.
	The user name and MAC binding	Support automatic binding of terminal access for the first time
	Data encryption	Support TKIP and AES (CCMP)
	EAP Protocol categories	Support EAP TLS, EAP PEAP, EAP - MD5, EAP - MSCHAPv2, etc.
	MAC static black and white list	Supported
	The dynamic blacklist	Supported
(ACL) Access Control Policy (ACL)	Multidimensional user access and role assignment	Support user access and role assignment based on access location; Support access and role assignment based on terminal types such as android, ios, windows, etc.; Support access and role assignment based on terminal MAC address; Support permission assignment based on user, and set different access permission for each specific user; Support permission assignment based on time bucket, and provide different access permission in different time bucket, which can flexibly control the access permission of the staff on and off duty; Support different access permissions based on user groups and temporary visitor groups; Support different access permissions based on visitors types such as authentication-free user, message visitors, WeChat visitors, WeChat + message authentication visitors; Support access control based on the Class Tunnel Private Group ID returned at user's Radius authentication; Support access control based on organizational unit, security group, and user name of LDAP;
QoS		
	Intelligent channel management	Support flow father and son channel technology, and support three-level father and son channel; Support channel limit and ensure the channel technology, dynamically adjust the channel bandwidth;
	Flexible and rational allocation of bandwidth resource	Support flow channel division and priority setting based on, user, and user group; Up and down flow control based on single user, with flow control granularity of 1 KBPS; Support flow control based on time, which distributes different flow strategy in different time, flexibly allocating bandwidth resources; Support intelligent average distribution of the user bandwidth in flow channels; Support flow control based on terminal access position, distributing different flow strategies at different access position; Support flow control based on terminal types such as android, ios, windows, etc.;
	802.11e/WMM	Support priority scheduling based on business application type (voice, video and data)
	The end-to-end QoS service	Supported
Radio frequency	Channel automatic and manual adjustment	Supported

management	Power automatic adjustment	Supported
	Power manual adjustment	Support adjustment with the granularity of 1 dBm, and the adjusting range is 1 dBm to the scope of power prescribed by the state;
	Radio frequency time opening or closing	Support radio frequency time opening or closing based on period of time;
	Load balanced between AP	Support load balancing based on users, flow rate and frequency band, realize 2.4 G and 5 G dual-band loads in the case of dual-band;
	Wireless coverage black hole detection and compensation	Supported
Security defense	WIDS/WIPS	Supported
	Illegal AP detection, inhibition	Supported
	Anti phishing	Supported
	Attack defense	Support the defense against the DoS attack, spoofing attack, and flooding attack
The loiter network preventing strategy	Online time control	Support online time control (to minutes)based on users, access position, and terminal type, can set time of taking effect (only calculating planned time specified, not calculating the online time out of the validity time, and the time of taking effect can be recycled or one-time).When the accumulative value reaches the threshold, it can refuse to use online service again in the control period or continue to use online service after blocking for a period of time
	Flow quota	Support flow quota (to MB) based on users, access position, and type of terminal, and you can set the daily quota and monthly quota, and can also set the start date of a month. When the accumulative value exceeds the quota, it can refuse to use online service again in the control period or continue to use online service after blocking for a period of time.
Wireless optimization	Electronic schoolbag scene optimization	To speed up multicast packets, and comprehensively improve scene effect of electronic schoolbag;
	Intelligent broadcasting speeding up	According to the practical environment, improve the transmitting speed of broadcast packets automatically, and speed up the transmission efficiency of broadcast packets;
	Prevent terminal dragging	Prevent low-speed terminal to lower overall speed of network based on time fairness algorithm;
	Prevent terminal viscosity	APPerceive the STA connected to AP, and intelligently guide STA to access to the best AP;
	Low rate of terminal access is prohibited;	Set a threshold for velocity of access terminal, to prohibit weak signal terminal access below a certain speed and improve overall speed of network
	High density access scene optimization	High-density optimization of dense area of wireless users (more than 40 terminals in the coverage of a single access point) can save a certain wireless air resources and improve overall performance of the AP;
	ARP turned to unicast	Turn ARP broadcast message into unicast, which can reduce broadcast packets and improve transmission speed.
	DHCP request to the wireless terminal is prohibited.	After start using this option, the broadcast message required by DHCP will be only forwarded to wired network, and won't be forwarded to the other wireless network, which can improve the throughput of the overall wireless network and improve the performance of wireless network.
	automatic VLAN segmentation	Support automatic VLAN division based on the users/user groups, AP access position/AP group, terminal type /MAC, RADIUS Class attribute value/Group ID, AD attribute value, and certificate attribute value, automatically distributing to the corresponding VLAN pool at terminal access;
authentication Webpage	WEB authentication page can self-define LOGO, background color, page word and disclaimer, and supports the switch between Chinese and English; before the WEB authentication (including several authentication methods such as Portal, we-chat, short message and two dimension code), full-screen advertisement illustration is supported to play; the countdown method is supported; after being forced to watch the advertisement display for certain time, the user is allowed to access to internet;	
Authentication page push	Terminal self-adaptation	Intelligently identify terminal type, and push the authentication page matching the terminal with the right the size;
	Authentication page push	Push different certification pages according to different SSID, access position, terminal types, and time.
	Skip to push after certification	Support skipping pages or skipping to the original page before certification after setting different certifications based on access position, terminal type users/user groups, and type of certification. Support to transmit information of user name, terminal MAC, IP, and access AP/AP group, used for secondary development or website statistical analysis.
	Data-push method	Support four kinds of data-push, namely WeChat, text messages, web page embedded, and full-screen web page, able to customize images, texts, hyperlinks, etc;
		Support marketing push based on the user behavior, the marketing push can match with the

Marketing push	Marketing of search behavior	key word searched by the user in Baidu, search engine collection, Sougou, Taobao and Jingdong to push the specific advertisement, and support the web page floating window, we-chat and short message.
	Marketing based on the online time	Support to push to online user messages, WeChat, and web advertising, and support to push only to the users with online time greater than a certain period of time and for a certain number of times;
	First access marketing	Intelligently identify the first access user, support to automatically push the preset messages and WeChat information to the first access user.
	Terminal marketing	Automatically calculate the occurrence number of customer terminal, and support to automatically push to the reappearing old customer the preset messages and WeChat information (can set to push to the users with offline time greater than a certain period of time and appearing for a certain number of times);
	Marketing based on the user's location	Support to set different push information for different AP, realize push based on access position or location change;
	Marketing based on the period	Support to push different advertising information in different time period, applicable to access rules such as online time, first access, terminal appearing, and access position.
	WeChat active marketing	It is internally installed with WeChat marketing platform, which supports to actively push directional messages to WeChat user (not mass texting without being limited by the number of times);
	SMS active marketing	It is internally installed with SMS marketing platform, which supports to actively push directional messages to text message users;
	Search analysis	Rank the search keywords according to searching times on Baidu, search.com, sougou.com, taobao.com and jingdong.com, to analyze customers' preference and propensity to consume.
	Marketing statistics	Make statistic of search behavior, first access, terminal appearing, and online time and total time and trend of push;
	Consumer flow analysis	Support to check statistics and trends of visiting customers(people), new visiting customers(people), new registered users (people), access users (people), visiting customer not for the first time, returning rate, and the average residence time (locally save a maximum of 90 days); Support to collect the information of terminal MAC, terminal types, occurrence time, and residence time of non-access users; Support to check statistic of residence time distribution; Support contrast figure according to time of the above data trend; Support to check the above information according to the AP group and divided area;
Consumer flow analysis	The original data export	Support export of original data on visitor flow analysis, including the scanned terminal type, terminal MAC, first appearing time, final appearing time, occurrence times and the terminal type, terminal MAC, first access time, last access time, access number of access terminal.
	Real-time display of AP dynamic information	Real-time display of each AP position, AP real-time status, number of access users, real-time flow, online user list, which is convenient for administrator to know real-time online health information.
Hot map	Architectural figure import	Support manual import of building figure, floor area distribution, and free allocation of AP sign location
	Visitor density	Support to display the regional traffic density and export images through thermodynamic diagram, by which the regional population distribution can be viewed.
Wired management	Access authentication	Support Web authentication, temporary visitor authentication, and access authentication without user authentication; Support IP address-based authentication method;
	AP wired port side access authentication	The same with wireless side access authentication, WEB WEB, WeChat authentication, and SMS authentication are supported.
	IP address and user name binding	IP address and user name binding are supported; Support automatic binding of access for the first time
	Acess Control Policy (ACL)	The same with wireless side, access rights allocation based on user accounts, user groups, time and external server properties are supported;
	Traffic management	The same with wireless side, traffic management based on, user accounts, user groups and time are supported;
	Embedded site investigation figure management software	Auto-completing AP point deployment according to import of deployment site scene graph is supported and reduce the project site investigation period and site investigation cost.
Site investigation management	AP-based access user quantity statistics	The number of connected users and change trends of each AP in the recent one day, one week, and one month can be measured.
Hotspot analysis	AP-based network flow analysis	The network flow and tendency changes of each AP in the recent one day, one week, and one month can be measured.
	AP-based signal quality analysis	Statistic analysis for the signal usage, noise, retransmit rate, BER, and BER change trends of each AP is supported.
		Supported



	Cross-WAN and cross-NAT remote AP deployment	
AP access methods	AC discovery methods	L2 and L3 discovery, DHCP option 43 and DNS domain name discovery are supported
	webAgent	Controller IP addresses can be dynamically discovered by using the webAgent technology. This avoids AP disconnection caused by unfixed controller IP addresses.
	Tunnel encryption	Supported
	Relay method	Point-to-point and point-to-multipoint supported
Wireless relay bridge	Relay frequency band	Support GHz 2.4G/5.8G2.4/5.8
	Disable wireless network on relay frequency band	Supported
	Wireless back-haul service	Supported
	Link aggregation	Up to eight of each group are supported and the maximum of eight groups are supported at the same time
Layer 2 Security	Line status monitoring	Supported
	ARP proxy	Supported
	DHCP	DHCP Client, DHCP server, DHCP relay and DHCP Snooping are supported.
L3 Security	Network access mode	static IP address, DHCP and PPPoE dial-up
	DNS proxy	Supported
	Static route	Supported
	Strategy route	Supported
High reliability	AP fast switching between AC	Supported
	DHCP server backup	Supported
	Authentication server backup	Supported
	Disaster backup	The function of AC and authentication server disaster backup (escape) is supported; when the failure occurs, the normal access of new users and the normal access to the Internet of users can be guaranteed.
	Management modes	WEB, CLI, Telnet, SSH, etc. and Chinese and English interface management are supported.
Network management and configuration	SNMP	SNMP v1/v2/v3, SNMP Traps
	Grading administrator	Super administrator, administrator and read-only administrator are supported.
	Status display	Support AC System Status Display AP and AP MESSAGE DISPLAY as well as; Online user information display;
	Warning mechanism	Port state warning; Network attack real-time warning; Double switch warning, etc.
	Traffic history query	AC and AC historical traffic query are supported.
	User quantity trend	Supported
	AP online and offline remind	Supported
	Record user online and offline information	Supported
	Firmware upgrade	AC firmware remote automatic or manual upgrade is supported;支持 AP 固件自动升级 AC firmware automatic upgrade is supported.
	Backup configuration and backup recovery	Supported
	System log management	

		The function of view and export system log
	Strategy troubleshooting function	Supported
	Restart the device and restarting service	Supported
	Configuration date and NTP service	Supported



**SANGFOR**  
深信服科技



**SUNDRAY**  
信锐技术

Sundray Technologies Co, Ltd.

Address: Building A1, i Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China Post.  
Post Code: 518055

**Service hotline: +86-755-86725911**

Web: [www.sangfor.com](http://www.sangfor.com); [www.sundray.com](http://www.sundray.com) E-mail: [liaohaibo@sundray.com](mailto:liaohaibo@sundray.com)

Documentation version: 20150701-V2.6

Copyright © 2015 Shenzhen Sundray Technologies Company Ltd. All rights reserved.

DISCLAIMER: Sundray Technologies retains the rights of final explanation and modification of this document and this statement.